


Extension sockets according to DIN 2187, hardened and tempered, precision ground internally and externally




Model No.	Morse taper		a1 mm	a2 mm	d1 mm	d2 mm	d3 mm	l1 mm	l2 mm	Packaging style	Weight g
	outside	inside									
BL11145	1	1	-	7	12,065	12,065	20	145	83	Individual box	190
BL12160		2				17,78	30	160	98		250
BL21160	2	1	-	9	17,78	12,065	20	160	85	Individual box	340
BL22175		2				17,78	30	175	100		400
BL23196		3				23,825	36	196	121		550
BL31175	3	1	5	-	23,825	12,065	20	175	81	Individual box	400
BL32194		2	-	9		17,78	30	194	100		840
BL33215		3	-	9		23,825	36	215	121		1000
BL34240		4	-	9		31,267	48	240	146		1300
BL41200	4	1	6,5	-	31,267	12,065	20	200	82,5	Individual box	800
BL42215		2	6,5	-		17,78	30	215	97,5		850
BL43240		3	-	10,5		23,825	36	240	122,5		1500
BL44265		4	-	10,5		31,267	48	265	147,5		1900
BL45300		5	-	10,5		44,399	63	300	182,5		2750
BL51232	5	1	6,5	-	44,399	12,065	20	232	82,5	Individual box	1600
BL52247		2	6,5	-		17,78	30	247	97,5		1600
BL53268		3	6,5	-		23,825	36	268	118,5		2840
BL54300		4	-	13,5		31,267	48	300	150,5		3310
BL55335		5	-	13,5		44,399	63	335	185,5		4200

Oil toughened extension sockets externally precision ground with hardened tang

Outside taper Morse DIN 228



Inside taper Morse DIN 228



Model No.	Morse taper		a1 mm	a2 mm	d1 mm	d2 mm	d3 mm	l1 mm	l2 mm	Packaging style	Weight g
	outside	inside									
BL11145OT	1	1	-	7	12,065	12,065	20	145	83	Individual box	190
BL12160OT		2				17,78	30	160	98		250
BL21160OT	2	1	-	9	17,78	12,065	20	160	85	Individual box	340
BL22175OT		2				17,78	30	175	100		400
BL23196OT		3				23,825	36	196	121		550
BL31175OT	3	1	5	-	23,825	12,065	20	175	81	Individual box	400
BL32194OT		2	-	9		17,78	30	194	100		840
BL33215OT		3	-	9		23,825	36	215	121		1000
BL34240OT		4	-	9		31,267	48	240	146		1300
BL41200OT	4	1	6,5	-	31,267	12,065	20	200	82,5	Individual box	800
BL42215OT		2	6,5	-		17,78	30	215	97,5		850
BL43240OT		3	-	10,5		23,825	36	240	122,5		1500
BL44265OT		4	-	10,5		31,267	48	265	147,5		1900
BL45300OT		5	-	10,5		44,399	63	300	182,5		2750
BL51232OT	5	1	6,5	-	44,399	12,065	20	232	82,5	Individual box	1600
BL52247OT		2	6,5	-		17,78	30	247	97,5		1600
BL53268OT		3	6,5	-		23,825	36	268	118,5		2840
BL54300OT		4	-	13,5		31,267	48	300	150,5		3310
BL55335OT		5	-	13,5		44,399	63	335	185,5		4200